

# Digital manometer

With integrated bar graph display

Accuracy 0.5 %



## Description

This digital manometer 3321 is the ideal solution for local digital display independent of the mains. The integrated battery allows measurements to be made independent of a fixed source of power.

Accuracy, reliability and mechanical resilience make the digital manometer suitable pressure measurement tasks in numerous applications.

The stepped measuring ranges extend from 2 bar up to the high pressure range of 700 bar. For pressure ranges above 50 bar, the casing and parts that come into contact with the measuring medium are made of stainless steel and thus resistant to attack from chemically aggressive media.

The additional integrated bar graph display with a trailing pointer function shows the trend in current working pressure directly. The model 3322 comprises a further 4,5-digit display for a direct readout of peak value, tare and other parameters. Internal lighting ensures the display is optimally for a clear readout even in unfavourable lighting conditions.

The buttons on the front are used for adjustment of the programmable parameters.

The digital manometer meets electromagnetic compatibility requirements (EMC) to EN 61326.

## Features

- Measuring ranges from 2 – 700 bar
- Fine step selection of nominal pressure ranges
- LC-Display with numerals 11 mm high
- Bar graph display with a trailing pointer function
- Tare function
- Password protection
- MIN/MAX memory
- Internal lighting
- High overload protection

## Measuring ranges

Overpressure  
Positive 0...2 bar up to 0...700 bar

## Area of use

Machine construction  
Plant and apparatus construction  
Hydraulics, pneumatics  
Measuring equipment monitoring

## Technical data

Series	3321	3322
Display - Range	7-segment LCD-display, 11 mm high 9999 digit bar graph display	7/14-segment LCD-display, 11 mm high 19999 digit second display 19999 digit, 7 mm high bar graph display
- Accuracy - Conversion rate	0,5% of F.S. $\pm 1$ digit <sup>1)</sup> 5/sec	0,5% of F.S. $\pm 1$ Digit <sup>1)</sup> 5/sec
Measuring ranges to EN	0...2 / 0...5 / 0..10 / 0..20 / 0..50 / 0..100 / 0..160 / 0..250 / 0..400 / 0..600 / 0..700 bar, others on request	
Type of pressure	positive and negative overpressure	
Overload limit	2-fold, max. 1000 bar	
Parts in contact with measuring medium	Measuring ranges $\leq 50$ bar stainless steel; Al <sub>2</sub> O <sub>3</sub> ; NBR; ceramic measuring cell Measuring ranges $\geq 100$ bar stainless steel only; thin-film type measuring cell	
Pressure union	G 1/4 B, 1/4 NPT, others on request	G 1/4" B, 1/4 NPT, rotatable (300°)
Stability per year	$\leq \pm 0,2\%$ of F.S. under reference conditions	
Peak value memory	MIN / MAX	
Progr. parameters - Tare - autom. Turn-off time  - measuring unit	without without, OPTION 15, 30, 60, 120 min factory set, Others on request bar, psi, MPa adjustable	$\leq \pm 20\%$ of F.S. adjustable adjustable  bar, psi, MPa adjustable
Display lighting	Without	with
Voltage supply - service life	2x 1,5V round cells AA 4000 hrs (AA 2000 mAh)	
Temperature comp. Range	0...60°C	
Temperature influence - zero point - Measuring span	$\leq \pm 0,15\%$ / 10 K $\leq \pm 0,15\%$ / 10 K	
Degree of protection - perm. rel. humidity	IP 65 acc. to EN 60529/ IEC 529 < 90%, non-condensing	
Emitted interference <sup>2)</sup>	Acc. To EN 61326	
Interference immunity <sup>2)</sup>	Acc. To EN 61326	
Temperature ranges - Storage - Measured medium - Ambient	-20 ... 70° C -20 ... 85° C (-30 ... 100° C with measuring range $\geq 100$ bar) -10 ... 60° C	
Case	Stainless steel, OPTION protective cap black	
Weight	Approx. 0,4 kg	

F.S. = full-scale reading

- 1) Meas. Deviation according to IEC 61298-2, including non-linearity, hysteresis, zero-point and final value deviation  
2) Declaration of conformity on request

## Dimensions (mm)

### Case

